

Bibliographic data: DE 10207276 (A1)

NEEDLE INSERTION DEVICE HAVING A TRANSVERSELY MOVING RETAINING ELEMENT

Publication 2003-09-11 date:

Application

documents:

STEFFEN BEAT ICHI: JOST STEFAN ICHI: PONZER RAINER ICHI: TSCHIRREN MARKUS ICHI Inventor(s):

Applicant(s): DISETRONIC LICENSING AG [CH] +

A61M5/32; (IPC1-7): A61M5/20; A61M5/32 - international: Classification:

- European: A61M5/32E

DE20021007276 20020221 number:

Priority DE20021007276 20020221 number(s):

 WO 03070303 (A2) WO 03070303 (A3) published as:

 WO 03070303 (A8) AU 2003201258 (A1)

Cited US5634906 (A) US5417662 (A)

Abstract not available for DE 10207276

Abstract of corresponding document: WO 03070303 (A2)

an implement (1) provided for administering an injectable product. The administering implement (1) comprises a product reservoir and a penetrating needle (3) that is connected to the reservoir. The

The invention relates to a needle insertion device for lik e needle insertion device comprises; a) a needle protective sleave (5), and, b) a retaining sleave (10/15), which is joined to the needle protective sieeve (5), can move in relation to said needle protective sleeve (5) along a common longitudinal axis (L) while being

displaced in an advancing direction, and into which the administering implement (1) can be inserted in such a manner that the penetrating needle (3) projects beyond the retaining sleeve (10/15) in the advancing direction; c) whereby the retaining steave (10/15) comprises at least one retaining element (16) that, by effecting a retaining engagement that can be released prevents an inserted administering implement (1) from axially moving in relation to the retaining sleeve (10/15). The invention is characterized in that; d) the resalning element (16) can transversely move in relation to the longitudinal axis (L) whereby being able to effect and release the retaining engagement.

Last updated: 26.04.2011 Worldwide Database 5.7.22; 92p

US5282793 (A)

US4639249 (A)

View